

KX-EX600PWY**ATEX Certificated Stainless steel Explosion proof Housing**

- Window adopt stainless steel, equipped windscreen wiper .
- Can load fixed focus or zoom camera .
- Windows glass surface process by nano technology . Well light transmittance. non-stick oil/dusty /water
- Low power consumption, the fuselage internal air convection heat dissipation design, can work continuously for a long time
- Usual : AC220V/DC12V , other Power mode can be customized .
- Made of 304 stainless steel material. apply to strong corrosive environment
- Well design for Explosion-proof, anti-corrosion, waterproof , suitable for indoor and outdoor environment

Ex-Level	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db
Ingress Protection level	IP66
Temperature range	-40°C~60°C
Relative humidity	≤95% (+25°C)
Atmospheric pressure :	80kpa~106 kpa
Thermostat System	Optional
Window area	Φ60mm
Internal dimensions	Φ100×290mm(length)
Supply voltage	DC12V/AC220V optional
Applicable environment	Apply to explosive gas and combustible dust environment
material	304 stainless steel(316, 316L for optional)
Inlet interface specifications	G3/4"x 2
Installation Method	Wall Hanging dyadic , fixed bracket , Pillar base